












# Overview of Products Range

		Inner width		Inner height		External width		External height		Pitch		Bending radius	
page		da mm	a mm	da mm	a mm	da mm	a mm	mm		mm	da mm	a mm	
<b>Serie Light</b> 	40	SR200	12	35	12	-	18	41	15	17	18	40	
	42	SR250L/LI/LE	15	50	17	-	26	61	23	29	28	100	
	44	SR30090/91/92	18	38	18,5	-	29	49	23,5	30	33	100	
	46	SR325LI/LE	40	103	25	-	57	120	38	45	50	150	
	48	SR325L	40	103	25	-	57	120	38	45	50	150	
	50	SR335L/LI/LE	40	150	35	-	56,5	166,5	50	52	65	200	
	52	SR339	40	76	39	-	60	96	50	35	50	100	
<b>Serie Medium</b> 	60	SR300A	15	75	18	-	27	87	23	30	40	120	
	62	SR300	14	36	18	-	30	52	23	30	40	120	
	64	SR305A	30	50	24	-	54	74	30	35	50	150	
	66	SR305	30	50	20	-	52	72	30	35	50	150	
	68	SR355A	45	95	31	-	74	124	43	40	75	200	
	70	SR355	45	95	30	-	74	124	45	40	75	200	
	72	SR400	40	60	25	-	62	82	35	40	50	150	
	74	SR435MI/ME	40	150	35	-	60	170	49	50	60	200	
	76	SR445MI/ME	50	362	45	-	72	384	64	67	75	300	
	78	SR660A	50	362	37	-	75	387	55	50	100	250	
	80	SR770A	45	357	60	-	80	392	78	70	150	300	
	82	SR475MI/ME	74	498	75,5	-	112	536	100,5	105	150	400	
<b>Serie Heavy</b> 	88	SR306	43	355	30	37	79	391	55	65	75	300	
	94	SR307	42	354	40	47	80	392	64	70	75	250	
	100	SR308	38	350	48	57	82	394	75	80	150	400	
	106	SR309	64	400	70	75,5	120	456	100	100	200	500	
	110	SR310	200	600	112	-	260	660	150	145	200	750	
<b>Serie Protection</b> 	114	SR325PI	10	103	25	-	57	120	38	45	75	150	
	116	SR335PI	40	150	35	-	56,5	166,5	50	52	65	200	
	118	SR435PI/PE	40	150	35	-	60	170	48	50	75	200	
	120	SR445PI/PE	50	362	45	-	72	384	64	67	100	300	
	122	SR445AI/AE	50	362	45	-	72	384	64	67	100	300	
	124	SR475PI/PE	74	374	75,5	-	110	410	100,5	105	180	400	
	126	SR660	50	150	36	-	79	179	55	50	100	250	
	128	SR770	85	250	51	-	120	285	78	70	150	300	
	130	SR306CI/CE	43	355	37	-	79	391	55	65	107	300	
	132	SR308CI/CE	38	350	57	-	82	394	75	80	180	400	
	134	SR309C	200	400	72	-	256	456	100	100	200	500	
136	SR309CI/CE	64	488	75,5	-	120	544	100	100	200	500		
<b>Serie Sliding</b> 	140	SR326	61	373	30	37	89	416	59	65	107	300	
	146	SR328	61	373	48	57	116	428	79	80	150	400	
	152	SR319	64	400	70	75,5	128	464	107	100	200	500	
	154	SR329	64	488	75,5	-	128	552	107	100	150	600	
	162	SR478PI/PE	74	498	75,5	-	112	536	106,5	105	150	400	
	166	M60	115	539	60,5	-	165	589	90	90	150	400	
	168	M80	115	539	80,5	-	195	619	117	110	200	700	
<b>Serie Robot</b> 	178	SR495	45	-	35	-	69	-	45	-	100	-	
	180	SR500	65	-	30	-	93	-	43	-	100	150	
	182	SR510TN	88	-	46	-	132	-	55-77	-	125	-	
	182	SR515TN	88	-	46	-	132	-	55-77	-	175	-	
	184	SR545	62	-	46	-	123	-	62	-	100	-	
	186	SR599	210	-	59	-	272	-	85	-	220	-	
<b>Serie Steel</b> 	192	BS2000	79	304	32	38	112	337	53	75	75	305	
	194	BS3000	106	306	52	58	142	342	74	95	150	535	
	196	BS3000LT	106	506	52	58	140	540	74	95	150	535	
	198	BS3000LC	106	506	52	-	140	540	74	95	150	535	
	200	BS3500	104	404	65	70	153	453	95	125	200	600	
	202	BS3500C	104	404	65	-	153	453	95	125	200	600	
	204	BS3500LT	104	504	65	70	148	548	95	125	200	600	
	206	BS3500LC	104	504	65	-	148	548	95	125	200	600	
	208	BS4000	150	500	112,5	115	216	566	145	180	250	1000	
	210	BS4000C	150	500	104	-	216	566	145	180	250	1000	
	212	BS4500	300	600	182	180	390	690	220	250	400	1500	

•= standard; O=on request

Self supported length		Max. travel length	Snap open cover		Enclosed design	Vertical separator	Horizontal separator	Ver./horiz. separator	Drilled frame	Diameter	
											
max m	kg		int. raggio	est. raggio						int. mm	est. mm
0,90	0,1	-	-	-	-	-	-	-	-	-	-
1,30	0,1	-	•	•	-	o	-	-	-	-	-
1,45	0,1	o	-	-	-	-	-	-	-	-	-
1,90	0,5	o	•	•	-	o	-	-	-	-	-
1,90	0,5	o	-	-	-	o	-	-	-	-	-
2,20	1	o	•	•	-	o	-	-	-	-	-
2,20	1	o	-	-	-	o	-	-	-	-	-
1,70	0,1	-	•	-	-	-	-	-	-	-	-
1,55	0,1	o	-	-	-	-	-	-	-	-	-
1,40	1	-	•	-	-	o	-	-	-	-	-
1,90	1	o	-	-	-	o	-	-	-	-	-
2,30	1	-	•	-	-	o	-	-	-	-	-
2,30	1	o	-	-	-	o	-	-	-	-	-
1,60	1	-	•	-	-	o	-	-	-	-	-
2,20	1	o	•	•	-	o	-	-	-	-	-
3,70	1	o	•	•	-	o	o	o	-	-	-
2,45	1	o	•	-	-	o	o	o	-	-	-
3,80	1	o	•	-	-	o	o	o	-	-	-
4,75	1	o	•	•	-	o	o	o	-	-	-
3,10	1	-	•	•	o	o	o	o	o	-	-
3,90	1	-	•	•	o	o	o	o	o	-	-
4,95	1	-	•	•	o	o	o	o	o	-	-
6,50	1	-	•	•	o	o	o	o	o	-	-
7,00	1	-	•	•	o	o	o	o	o	-	-
1,70	0,5	-	•	-	•	o	o	o	-	-	-
2,00	1	-	•	-	-	o	-	-	-	-	-
2,10	1	-	•	•	•	o	o	o	-	-	-
3,35	1	-	•	•	•	o	o	o	-	-	-
3,35	1	-	•	•	•	o	o	o	-	-	-
4,45	1	-	•	•	•	o	o	o	-	-	-
2,30	1	-	•	-	•	o	o	o	-	-	-
3,45	1	-	•	-	•	o	o	o	-	-	-
2,70	1	-	•	•	•	o	o	o	-	-	-
4,00	1	-	•	•	•	o	o	o	-	-	-
5,80	1	-	-	•	•	o	o	o	-	-	-
6,00	1	-	•	•	•	o	o	o	-	-	-
-	-	•	•	•	o	o	o	o	o	-	-
-	-	•	•	•	o	o	o	o	o	-	-
-	-	•	•	•	-	o	o	o	o	-	-
-	-	•	•	•	o	o	o	o	-	-	-
-	-	•	•	•	-	o	o	o	o	-	-
-	-	•	•	•	-	o	o	o	-	-	-
-	-	-	•	-	-	-	-	-	-	600	755
-	-	-	•	-	-	o	-	-	-	630	830
-	-	-	•	-	-	•	-	-	-	940	1220
-	-	-	•	-	-	•	-	-	-	1060	1340
-	-	-	•	-	-	•	o	o	-	485	760
-	-	-	•	•	-	•	o	o	-	1400	2000
5,40	1	-	-	-	o	o	o	o	•	-	-
6,20	1	-	-	-	o	o	o	o	•	-	-
5,50	1	-	-	-	o	o	o	o	•	-	-
5,00	1	-	-	-	•	o	o	o	-	-	-
9,10	1	-	-	-	o	o	o	o	•	-	-
8,90	1	-	-	-	•	o	o	o	-	-	-
7,25	1	-	-	-	o	o	o	o	•	-	-
x,xx	1	-	-	-	•	o	o	o	-	-	-
10,50	1	-	-	-	o	o	o	o	•	-	-
9,70	1	-	-	-	•	o	o	o	-	-	-
13,00	1	-	-	-	o	o	o	o	•	-	-





CABLE **CHAINS** CABLE **CHAINS** CABLE **CHAINS** CABLE **CHAINS**

[www.brevettistendalto.com](http://www.brevettistendalto.com)

Your local distributor



**Brevetti Stendalto S.p.A.**

Viale G.B. Stucchi 66/8  
20900 Monza (MB) Italy  
Tel. +39 039 204901  
Fax +39 039 834250  
Internet: [www.brevettistendalto.com](http://www.brevettistendalto.com)  
E-mail: [info@brevettistendalto.it](mailto:info@brevettistendalto.it)